

No. AJFS1810009829FF

Date: OCT.29, 2018

Page 1 of 5

The following sample(s) was / were submitted and identified on behalf of the client as:

Sample Description: WHITE WOVEN FABRIC ADP-3020

Color: WHITE

Thickness: 0.2mm

Style/Item No.: ADP-3020 Composition: 100%P

Country of Destination: GERMANY

## Test Requested:

To determine the flammability (building materials class B1) in accordance with DIN 4102-1 (May 1998) Fire behaviour of building materials and elements Part 1: Classification of building materials, Requirements and testing

Test Results: -- See attached sheet -

<u>Classification</u>: The tested sample **meets** class **B1** building materials requirements of DIN 4102-1 (May 1998).

### **Test Period:**

Sample Receiving Date

: OCT.11, 2018

中国・浙江・安吉县阳光工业园二区阳光大道301号

Test Performing Date

: OCT.11, 2018 TO OCT.24, 2018

Signed for and on behalf of SGS-CSTC Co., Ltd. Anji Branch

Allen Zou

Technical Manager



邮编:313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com



No. AJFS1810009829FF

Date: OCT.29, 2018

Page 2 of 5

### I. Test conducted

This test was conducted as per DIN 4102-15:1990 DIN 4102-16:1998 and DIN 4102-1:1998 Clause 6.2, and Classification in according to DIN 4102-1 (May 1998) Clause 6.1-Class B1 materials.

## II. Sample details

Sample description / Color	Fabric / White	
Density	About 147 g/m <sup>2</sup>	
Size of sample	1000mm×190mm & 190mm×90mm	

## Conditioning

Prior to testing, the sample was conditioned at least 14 days to constant mass at a temperature of  $23 \pm 2$  °C, and a relative humidity of  $50 \pm 6$  %.

## III. Test results

## 1) "Brandschacht" Test according to DIN 4102-15 &16

Exposed surface: The front face

10	Results of "Brandscha	acht" Test (	(part 1)			
Line		Unit	Test assemblies No.			
No.		Offic	Lengthwise	Widthwise		
1	Specimen fixings according to DIN 4102 part 15, table	1				
2	Max. flame height above lower sample edge;	cm	30	30		
3	Time 1)	min:s	00:10	00:08		
	Melting/burning through		/	/		
4	Time 1) 1	min:s	00:01	00:01		
	Back of specimen		/	1		
5	Flaming/glowing, Time 1)	min:s	00:01	00:01		
6	Discolouring, Time 1)	min:s	00:01	00:01		
	Burning droplets		Yes	Yes		
7	Begin 1)	min:s	00:03	00:02		
	Amount		/	/		
8	Specimen material falling off in separate droplets		√	~		
9	Specimen material falling off continuously		/	/		

To be continued...



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overlead, available on request or accessible at hit by lewes age, coming firms and Conditions ago and, be deteriors format documents subject to Terms and Conditions for Electronic Documents at hits //www.ago.com/en/Terms-end-Conditions/Terms-b-Document agos Attention is drawn to the imitiation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document I advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and this document on excender and experience of the company and contained the company and the company an

No. 301, Sunlight Road, 2 Block Sunlight Industry Zone, Anji County, Zhejang Province, China 313300 t (多-572) 5018625 f (多-572) 5018626 www.spsgroup.com.cn 中国 - 新江 - 安吉县阳光工业园二区阳光大道301号 邮编:313300 t (多-572) 5018625 f (多-572) 5018629 e sgc.china@sgs.com



No. AJFS1810009829FF

Date: OCT.29, 2018

Page 3 of 5

10	Results of "Brandscha	acht" Test	(part 2)		
Line		Unit	Test asse	mblies No.	
No.		Offit	Lengthwise	Widthwise	
	Burning parts		No	No	
10	Begin 1)	min:s	1	- /	
11	Parts of sample falling off separately		1	/	
12	Parts of sample falling off continuously		/	/	
13	Duration of continued combustion on mesh base (max.)	min:s	No	No	
	Burner flame impairment by dripping/falling material		No	No	
14	Time 1)	min:s	/	/	
	Premature ending of test		1	/	
15	End of burning at specimen 1)	min:s	/	/	
16	Time when test terminated (if applicable) 1)	min:s	1	/	
	Burning after end of test		No	No	
17	Duration	min:s	/	/	
18	Number of specimens	-	*/	/	
19	Front of specimen		/	1	
20	Back of specimen		1	/	
21	Height of flame	cm	1	- 1	
	Glowing after end of test		No	No	
22	Duration	min:s	/	1 .	
23	Number of specimens	. [	1	1	
24	Front of specimen		1	/	
25	Back of specimen		1	/	
26	Top half of specimen		/	/	
27	Bottom half of specimen		/	/	

To be continued...



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overlead, available on request or accessible at <a href="https://www.sgs.com/en/Terms-and-Conditions.aspx.and">https://www.sgs.com/en/Terms-and-Conditions.aspx.and</a>, for electronic format documents applicable to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's sindings at the lime of its intervention yand within the limits of client's instructions, if any. The Company's accessing the sinding of the limit is of client's instructions, if any. The Company's sindings is to its Client's instructions, if any. The Company's sindings is to its Client's instructions, if any. The Company's sindings is to its Client's instructions, if any. The Company's sindings is to its Client's instructions, if any. The Company's sindings is to its Client's instructions, if any. The Company's sindings is to its Client's instructions, if any it is company is a sinding is to its Client's instructions. If any it is to the company is to the company is the company in the company is the c

No. 301, Sunifor(Roat, 2 Blox), Sunifor(Industry Zone, Air) County, Zhejang Province, Chine 3 13300 t (86-572) 501825 f (86-572) 501825 www.sgsgroup.com.cn 中国 - 新江 - 安吉县阳光工业図二区阳光大道301号 邮網:313300 t (86-572) 501825 f (86-572) 5018269 e sgs.china@sgs.com



No. AJFS1810009829FF

Date: OCT.29, 2018

Page 4 of 5

Line		Linit	Test assemblies No.				
No.		Unit —	Lengthwise /		Widthwise /		
	Residual length						
28	Single results	cm	71	69	71	70	
20	26 Single results	GIII	73	73	72	73	
29	Average of the single results	cm	71	.5	71.5		
*5	Smoke temperature		/		, /		
30	Max. of average	℃	139.6		141.2		
31	Time 1)	min:s	03:45		03:16		

Note: 1) time from start of testing

\*Reduction in number of test (DIN 4102 Part 16, clause 5.2)

Class B1 materials:

If the residual length measured after the first test is 45cm or greater, further tests are not required.

# 2) Normal Flammability Test according to DIN 4102-1 Clause 6.2

Edge ignition

Fire application time: 15s

S	Lengthwise					Crosswise				
Parameter	1	2	3	4	5	6	7	8	9	10
Whether or not flaming extinguished before reach the gauge mark(Yes/No)	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Whether or not flaming reach the measuring mark within 20 seconds(Yes/No)	No	No	No	No	No	No	No	No	No	No
Time for the flame tip to reach the gauge mark(s)	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Afterflame time (s)	0	0	0	0	0	0	0	0	0	0
Max. flame height (cm)	2	3	2	2	1	2	1	1	2	2
Molten dripping(Yes/No)	No	No	No	No	No	No	No	No	No	No
Smoke developments (visual impression)										

Note:

NA---Not applicable

To be continued...



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overfeaf, available on request or accessible at <a href="https://www.sgs.com/en/Terms-and-Conditions.aspx.and">https://www.sgs.com/en/Terms-and-Conditions.aspx.and</a>, for electronic format documents, aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of his document is advised that information contained hereon reflects the Company's findings at the time of the content of the document is advised that information contained hereon reflects the Company's findings at the time of the company of the content of the company of the company is decided to the company of the company. Any unsultantized alteration, foreger of efficient on the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless described the results shown in this test report refer only to the sample(s) are retained for 30 days only results shown in this test report refer only to the sample(s) are retained for 30 days only results shown in this test report of refer only to the sample(s) are retained for 30 days only results shown in this test report of refer only to the sample(s) are retained for 30 days only results shown the training of 30 days only results shown the retained of 30 days only results shown the retained of 30 days only results shown the retained of 30 days only results shown the results shown the sample(s) are retained for 30 days only results shown the results shown the retained for 30 days only results shown the results shown the retained for 30 days only results shown the results shown

1443。c email: CN Doschechtess.scor.
No.01.S.night Road; 28bx, Sunight housely Zens, Api County, Zhejiang Province, China 313300 t (86-57) 5/18825 f (86-57) 5/18825 e esps.china@ags.co
中国 - 浙江 - 安吉县阳光工业园二区阳光大道301号 邮编:313300 t (86-57) 5/18825 f (86-57) 5/18826 e esps.china@ags.co



No. AJFS1810009829FF

Date: OCT.29, 2018

Page 5 of 5

#### IV. DIN 4102-1:1998 Criteria for classification

- 1) All materials, except flooring, may be classed as **B1** materials if they meet the following requirements a) and b):
- The test using the 'Brandschacht' apparatus described in DIN 4102-15 (cf. subclause 6.1.3.1) shall be deemed passed if
- The mean value for the residual length (portion of specimen that has not burned or charred; cf. subclause
- 9.1 of DIN 4102-16) of each specimen is at least 15 cm and no individual values are lower than 0 cm,
- The mean effluent temperature does not exceed 200 ℃ in any test,
- The requirement for the residual length of each specimen is met even where there is afterflame, afterglow, or smouldering.
- b) Pass DIN 4102-1: 1998 sub-clause 6.2.3 Ignitability Test if For each specimen, flaming doesn't reach the gage mark within 20s after flame application.
- 2) Materials may be classed as **B2** materials if they pass the ignitibility test specified in DIN 4102-1: 1998 subclause 6.2.5.

For each specimen, flaming doesn't reach the gage mark (150mm marks) within 20s after flame application.

3) Combustible materials which cannot be classed as B1 or B2 materials shall be classed as B3 materials.

### STATEMENTS:

This test report does not replace any mandatory certification of the product that may be required.

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test; they are not intended to be the sole criterion for assessing the potential fire and smoke hazard of

### Photo Appendix:

the product in use.



SGS authenticate the photo on original report only

\*\*\* End of Report \*\*\*



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sis.com/en/Terms-and-Conditions.aspx.and, restorations for Electronic Documents at http://www.sis.com/en/Terms-and-Conditions/Terms-and-C

No. 301, Sunlight Road, 2 Block Sunlight Industry Zone, Inc. (County, Zinejang Province, China 313300 t (186-572) 501882 f (86-572) 501882 www.sepsgroup.com.cn 中国·新江·安吉县阳光工业园三区阳光大道301号 邮编:313300 t (86-572) 501882 f (86-572) 501882 e sgs.china@sgs.com